

520 gsm PVC Polished finish- 152 cm



Black



Red



White



Green



Blue



Yellow

Base fabric: 460 Decitex Woven Polyester 64gsm
Coating: Laminate of Flexible PVC on each side of scrim fabric
Total mass: 520gsm (+/- 25)
Finish: Polished
Roll length: 50m

Physical properties tested in accordance with BS 3424 "Methods of test for coated fabrics"

TENSILE STRENGTH: Part 4, Method 6	Warp 930 N/50mm Weft 930 N/50mm	FLAMIBILITY:	Complies with BS5876 Part 2 Type A when Tested by BS5438 Test 3
TEAR STRENGTH: Part 5 Method 7B	Across Warp 290N Across Waeft 250N	WATER PENETRATION:	Minimum 1500mm
COATING ADHESION: Part 7 Method 9B	25N/50mm	CHEMICAL RESISTANCE:	Generally Satisfactory
COLD CRACK: Part 8 Method 10A	Not higher than -25°C	FLEX RESISTANCE: Part 9 Method 11B	5000,000 flexes minimum to meet the requirements of ISO 7854 1984 (Method B)

These are typical results intended for guidance only
Conforms with BS3408/20

www.mitco.co.uk

tel. 0141 773 5469

fax. 0141 773 5455

email. info@mitco.co.uk