

HYTEX RM 12 SDC

Cotton / Canvas- Dry Chemical, Rot & Water proof



Olive



White



Green

Weight:	12 oz / 525 gsm (+/- 5)	
Width:	91 cm	BS2286
Roll length:	approx. 100 m	

PHYSICAL PROPERTY	SPEC.	TOL	TEST METHOD
Bath test- leakage (mls)	Nil	-	Internal
Bath test- Absorbtion (%)	16 max	-	Internal
Crushed cone test- leakage (mls)	Nil	-	Def Stand. 83-27 lss
Cone test- Absorbtion (%)	Nil	-	"
Dimensional change- weft 5 x 50c (%)	2.5	+/-1	ISO 7771 BS 4736
Dimensional change- warp 5 x 50c (%)	2.5	+/-1	"
Hydrostatic head tested (10cm / min)	60		ISO 811
Flammability- bottom edge	limmited	-	-
Flammability (after soaking)- bottom edge	limmited	-	-
Rotproof content	Pass	-	BS 2087 PT2- 6.5 METH. 5
Spray rating	3		ISO 4920 BS EN24920
Tensile Strength, Warp (N)	1500	-	EN ISO 13934-1
Tensile Strength, Weft (N)	1000	-	"
Wing Rip Tear, Warp (N)	35	-	EN ISO 13937-3
Wing Rip Tear, Weft (N)	30	-	"

tel. 0141 773 5469

fax. 0141 773 5455

email. info@mitco.co.uk

www.mitco.co.uk

1